





# **Parameters**

SPECIFICATION						
Item	<b>P</b> 3	P4	P5	<b>P</b> 6	P7.62	
Pixel pitch	3 mm	4 mm	5 mm	6 mm	7.62 mm	
LED type	SMD 3 in 1	SMD 3 in 1	SMD 3 in 1	SMD 3 in 1	SMD 3 in 1	
Pixel density	111111 pixels/m2	62500 pixels/m2	40000 pixels/m2	27777 pixels/m2	17222 pixels/m2	
Pixel conÞguration	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B	
Module dimension(WxH)	192x192mm	256x128mm	320x160mm	192x192mm	244x244mm	
Module resolution	64x64	64x32	64x32	32x32	32x32	
Cabinet dimension(WxHxD)	768x768x100mm	768x768x100mm	960x960x100mm	960x960x100mm	976x976x100mm	
Cabinet resolution	256x256	192x192	192x192	160x160	128x128	
Screen weight	35kg/m2	35kg/m2	35kg/m2	35kg/m2	35kg/m2	
View angle	H140°/ V140°	H140°/ V140°	H140°/ V140°	H140°/ V140°	H140°/ V140°	
Best viewing distance	3	4	5	6	7.62	
Brightness	800 ~ 1000					
Gray scale	14					
Colour temperature	3200~9300					
Refresh rate		960 ~ 1920				
Contrast ratio	4000 : 1					
Power supply	100~240V					
Storage temp	-20°C~+60°C					
Operation temp	-20°C~+50°C					
Operation humidity		5%~95%RH				
Input signal	DVI / VGA , RGBHV, Composite Video signal , S-VIDEO, YPbPr(HDTV)					
Driving method	1/32 dynamic	1/16 dynamic	1/16 dynamic	1/16 dynamic	1/8 dynamic	
Max. Power consumption	800W/m2	800W/m2	800W/m2	800W/m2	800W/m2	
Avg. Power consumption	280W/m2	280W/m2	280W/m2	280W/m2	280W/m2	





# **Indoor Advertising LED Screen**

CI Series is indoor LED screen used for supermarket and window shop LED screens for businesse promotion.

#### Features



High resolution





Various applications





Wide viewing angle



Front & rear access



Custom screens




# High resolution

These big indoor LED screens are available in a very small pixel pitch, so they will offer very sharp image and videos.



# Various applications accepted

These types of screens are not water proof, so they are mostly used for shop windows and stores, shopping centers, screens intalled in walls and hanging screens.



# Front & rear access

Magnetically mounted modules and a user-friendly supplied access tool ensures that maintenance can be conducted officiently and quickly. All components can be accessed from the front so ideal for surface mounted installations.





Indoor Fixed LED Screen CI



# Brightness adjustable

Indoor LED screens support adjusts the brightness, which is generally 256-level adjustable, it works under day time and night time environment.



## Wide viewing angle

Indoor LED displays provide wider viewing angles and pixel-perfect imagery which is a real advance over the traditional LCD and DLP video walls.



### Custom screens

we manufacture custom indoor LED screens, so you can make the most of them. While the big indoor led screens on the contrary able to cover a large area and can be manufactured in fully customized sizes.



## LED Screen Manufacturer in China





#### **SHENZHEN BIBI LED CO LTD**

Mob: +86 153 9990 6913 Web: www.bibiled.com E-mail: info@bibiled.com

Address

The Building C, Tangtou Industrial Park, Shiyan Town, Baoan District, Shenzhen.

